

Gasche Resilient Thread Pressure Vessels



At A Glance

Designed for extreme conditions of pressure and temperature where cycling is involved.

ID range:

8" to 48"

(203 mm to 1219 mm)

Pressure ranges:

2,000 psi to 48,000 psi

138 bar to 3309 bar

Gasche Resilient Thread Closure

Many high pressure processes require cyclic operation, in which the vessels must be charged, closed, heated, pressurized, then cooled, depressurized and opened. Such cyclic operation may be required once a day or several times an hour. In addition, there is an increasing need for pressure vessels that can operate at extremely high pressures and elevated temperatures.

To meet the application requirements, pressure vessel design must, in many cases, make use of materials with different coefficients of expansion. During elevated temperature operation, these differing coefficients of expansion cause additional stresses that are difficult to overcome by conventional means. Repeated cycling can also cause deformation of closure components that may reduce cyclic life.

Extensive investigations of various closure designs were conducted jointly by Parker Autoclave Engineers and an independent analyst.

The fact was established that with the conventional threaded closures, stresses are concentrated at the base of the closure - on the first or second bottom threads. Parker Autoclave Engineers has determined that this concentration of stress is greatly reduced by introducing flexibility into the thread.

The required resiliency is provided by using a flexible high quality spring to form the thread.


The resilient spring consists of a solid wound spring with an inner steel rod core forming the equivalent of an integral thread. The main nut incorporates a semi-circular helical groove that receives the resilient spring assembly. Thus the main nut can be engaged with the body of the vessel as with any conventional design.

Even large covers can be turned manually because of rounded surface of the resilient thread. Turning is facilitated by the slight clearance between the inside diameter of the body opening and the outside diameter of the main nut.

The Resilient Thread Closure answers the conditions imposed by modern high pressure processes, with performance proven in actual operation.


Parker Autoclave Engineers designs and manufacturers pressure vessels to suit many applications. Sizes, temperature and pressure parameters and materials will vary widely because of the customers individual needs. For information regarding your specific application requirements please contact the factory.

Range of Specifications




Resilient straight thread vessels with dual o-ring seal:

The resilient straight thread closure distributes the load more evenly across the entire threaded area. The straight thread closure with o-ring seal is used in applications requiring high pressure at moderate to low temperature.



Tapered, resilient thread closure with dual o-ring seal:

The tapered resilient thread not only spreads the load more uniformly across the closure, but also provides for quick opening and closing of the pressure vessel. It requires approximately 2-1/4 turns to open or close.



Resilient straight thread vessel with self-energizing closure:

Non-tapered, resilient straight thread closure vessel with self-energizing closure is particularly suited to high pressure, high temperature cyclic operating conditions. A modified Bridgman, AE self sealing resilient thread closure permits accelerated heating and cooling of the pressure vessel, and also compensates for thermal and pressure fluctuations during operation.

WARNING

FAILURE, IMPROPER SELECTION OR IMPROPER USE OF THE PRODUCTS AND/OR SYSTEMS DESCRIBED HEREIN OR RELATED ITEMS CAN CAUSE DEATH, PERSONAL INJURY AND PROPERTY DAMAGE.

This document and other information from Parker Hannifin Corporation, its subsidiaries and authorized distributors provide product and/or system options for further investigation by users having technical expertise. It is important that you analyze all aspects of your application and review the information concerning the product or system in the current product catalog. Due to the variety of operating conditions and applications for these products or systems, the user, through its own analysis and testing, is solely responsible for making the final selection of the products and systems and assuring that all performance, safety and warning requirements of the application are met. The products described herein, including without limitation, product features, specifications, designs, availability and pricing, are subject to change by Parker Hannifin Corporation and its subsidiaries at any time without notice.



信德迈科技(北京)有限公司 CNMEC Technology

地址：北京市朝阳区望京SOHO-T1-C座2115室

邮编：100102

*Tel: 010-8428 2935 | * Fax: 010-8428 8762

*手机：139 1096 2635

*电子邮件：sales@cnmec.biz

主页：<http://www.cnmec.biz>



ISO-9001 Certified

Bulletin PV-RT