



Interconnects with similar plastic latch push button couplings.

PPA Series Couplings are general purpose, thermoplastic couplings. The PPA couplers are push-to-connect and have a plastic latch for push-button release. With a fully plastic exterior and smooth face, they are non-marring to most surfaces. Note: Does not interchange with PPL Series.

**Applications include:**

- Medical Devices
- Laboratory Equipment
- Chemical Processing
- Food and Beverage
- Industrial
- Process Equipment

**PPA Series Specifications**

Flow Capacity	Rated Pressure	Temperature	Material Body & Latch	Material Springs	O-ring
1/4"	Vacuum to 120 PSI	-40° to +180° F -40° to +82° C	Acetal Copolymer	Stainless Steel	Nitrile

**Couplers- Hose Barb**

Body Size	Valved Coupler					Non-Valved Coupler				
	Part Number	Valved	Port End	L	H	Part Number	Valved	Port End	L	H
1/4	PPA-251-4HB	Yes	1/4" Hose Barb	2.03	0.93	PPA-253-4HBSB	No	1/4" Hose Barb	1.36	0.93
1/4	PPA-251-6HB	Yes	3/8" Hose Barb	2.04	0.93	PPA-253-6HBSB	No	3/8" Hose Barb	1.36	0.93

**Nipples- Hose Barb**

Body Size	Valved Nipple					Non-Valved Nipple				
	Part Number	Valved	Port End	L	H	Part Number	Valved	Port End	L	H
1/4	PPA-252-4HB	Yes	1/4" Hose Barb	1.89	0.71	PPA-254-4HB	No	1/4" Hose Barb	1.35	0.63
1/4	PPA-252-6HB	Yes	3/8" Hose Barb	1.75	0.71	PPA-254-6HB	No	3/8" Hose Barb	1.36	0.61